

A-C650

COMPONENT SPEAKER SYSTEM OWNER'S MANUAL

Thank you for purchasing a **AWAVE** Component Speaker. It is a state-of-the-art product specifically designed and engineered for vehicle use, and has been thoroughly tested to ensure consistent and reliable performance.

Should you have any questions regarding the installation or operation of your **AWAVE** Component Speaker, which are not answered in this manual, please contact your dealer for assistance.

## **FEATURES**

6.5" 2 Way Component Speaker Rms.Power: 80W Rubber Edge Paper Cone 4 ohm 1" Aluminum Voice Coil 10 Oz Magnet Structure 20mm Silk Dome Tweeter Rubber Magnet Cover

## **PRECAUTIONS**

- Before making holes, check the mounting space with supplied template.
- To prevent noise pick-up, keep the wiring away from motors, highvoltage leads and other potential noise sources.
- To prevent a short-circuit, keep all wiring away from moving parts and sharp edges.
- Make sure you carefully read and understand the installation instructions before installing this subwoofer in your vehicle.

| SPECIFICATIONS         | A-C650                 |
|------------------------|------------------------|
| Rms.Power (W)          | 80                     |
| Fo (Hz)                | 60                     |
| Nominal Impedance (Ω)  | 4                      |
| Sensitivity@1w/1m (dB) | 88                     |
| Frequency Range        | 60Hz∼20KHz             |
| Magnet                 | 10 Oz                  |
| Voice Coil             | 1"                     |
| Cone                   | Rubber Edge Paper Cone |
| Mounting Depth (mm)    | 52                     |
| Mounting Diameter (mm) | 142                    |